

Product Specification

ZPX08 Datasheet



Analog Port IP PBX Product.
Document Version 1.2

ZPX08 is a 8-ports analog IP PBX. Based on the Asterisk open source platform with excellent echo canceller function.

Specification:

| | |
|------------------|-------------------|
| Name | ZPX08 |
| Main board | 1 |
| Interface | 1*Power connector |
| | 2*RJ45 10/100M |
| | 1*MMC/SD slot |
| | 1*USB2.0 |
| | 8*RJ11 |
| Modules Support | FXS-200/FXO-200 |
| Size(mm) | 237*120*36 |
| Package Size(mm) | 290*254*60 |
| Weight(kg) | 1.5 |

Model No.:

| Model | ZPX0808 | ZPX0826 |
|---------|---------|---------|
| FXS-200 | 0 | 1 |
| FXO-200 | 4 | 3 |
| Model | ZPX0844 | |
| FXS-200 | 2 | |
| FXO-200 | 2 | |

Description:

- ◆ Modules Design: Up to 4 Dual FXS/FXO ports or mixed Dual FXS/FXO ports per card.
- ◆ Scalable: Just add additional cards to extend system.
- ◆ Easy to use: Easy operation with Web GUI.
- ◆ Global usable: Configurable line interface to meet global telephone line interface requirements.
- ◆ High quality with low price.
- ◆ PBX function: IVR, Voicemail, Conference bridge, Fax(T.38), etc

Features:

- ◆ Up to 30 concurrent calls.
- ◆ 8 Analogue lines can be Dual FXS or Dual FXO.
- ◆ VoIP ready.
- ◆ Web based management

Hardware and Software Requirements:

- ◆ 32bit embedded DSP CPU
- ◆ Four analog FXS-200/FXO-200 modules
- ◆ 256Mbytes FLASH
- ◆ 64Mbytes SDRAM
- ◆ Adapter In: 100~240V AC
Out: +12V DC, 2A
- ◆ uClinux 2.6.X
- ◆ Asterisk 1.4.21

Zycoo IT Co.,Ltd
Tel: 86-28-85334096
Fax: 86-28-85336721
www.zycoo.com