? OSSBox ?? Ubuntu Linux 8.10?

????

```
root@xbmc:~#
root@xbmc:~# lsb_release -a
No LSB modules are available.
Distributor ID: Ubuntu
Description:    Ubuntu 8.10
Release:        8.10
Codename:       intrepid
root@xbmc:~#
```

CPU ??

```
root@xbmc:~# cat /proc/cpuinfo
processor       : 0
vendor_id       : CentaurHauls
cpu family      : 6
model           : 9
model name      : VIA Nehemiah
stepping        : 8
cpu MHz         : 532.000
cache size      : 64 KB
fdiv_bug        : no
hlt_bug         : no
f00f_bug        : no
coma_bug        : no
fpu             : yes
fpu_exception   : yes
cpuid level     : 1
wp              : yes
flags           : fpu vme de pse tsc msr cx8 sep mtrr pge cmov pat mmx fxsr sse up rng rng_en ace ac
e_en
bogomips        : 1069.60
clflush size    : 32
power management:

root@xbmc:~#
```

RAM ??

```
root@xbmc:~#
root@xbmc:~# cat /proc/meminfo
MemTotal:         222168 kB
MemFree:           52720 kB
Buffers:            3124 kB
Cached:            54228 kB
SwapCached:        15296 kB
Active:            82376 kB
Inactive:          23972 kB
HighTotal:             0 kB
HighFree:              0 kB
LowTotal:         222168 kB
LowFree:           52720 kB
SwapTotal:        650592 kB
SwapFree:         500472 kB
Dirty:               720 kB
Writeback:             0 kB
AnonPages:         46460 kB
Mapped:            26276 kB
Slab:              15816 kB
SReclaimable:       6060 kB
SUnreclaim:         9756 kB
PageTables:         2664 kB
NFS_Unstable:          0 kB
Bounce:                0 kB
WritebackTmp:          0 kB
CommitLimit:      761676 kB
Committed_AS:     419668 kB
VmallocTotal:     798712 kB
VmallocUsed:       89572 kB
VmallocChunk:     708596 kB
HugePages_Total:       0
HugePages_Free:        0
HugePages_Rsvd:        0
HugePages_Surp:        0
Hugepagesize:       4096 kB
DirectMap4k:      188352 kB
DirectMap4M:       40960 kB
root@xbmc:~#
```

PCI Slot ??

```
root@xbmc:~# lspci
00:00.0 Host bridge: VIA Technologies, Inc. VT8623 [Apollo CLE266]
00:01.0 PCI bridge: VIA Technologies, Inc. VT8633 [Apollo Pro266 AGP]
00:08.0 Multimedia controller: Sigma Designs, Inc. EM8475 REALmagic DVD/MPEG-4 A/V Decoder (rev 03)
00:0a.0 Ethernet controller: Realtek Semiconductor Co., Ltd. RTL-8139/8139C/8139C+ (rev 10)
00:10.0 USB Controller: VIA Technologies, Inc. VT82xxxxx UHCI USB 1.1 Controller (rev 80)
00:10.1 USB Controller: VIA Technologies, Inc. VT82xxxxx UHCI USB 1.1 Controller (rev 80)
00:10.2 USB Controller: VIA Technologies, Inc. VT82xxxxx UHCI USB 1.1 Controller (rev 80)
00:10.3 USB Controller: VIA Technologies, Inc. USB 2.0 (rev 82)
00:11.0 ISA bridge: VIA Technologies, Inc. VT8235 ISA Bridge
00:11.1 IDE interface: VIA Technologies, Inc. VT82C586A/B/VT82C686/A/B/VT823x/A/C PIPC Bus Master ID
E (rev 06)
00:11.5 Multimedia audio controller: VIA Technologies, Inc. VT8233/A/8235/8237 AC97 Audio Controller
 (rev 50)
00:12.0 Ethernet controller: VIA Technologies, Inc. VT6102 [Rhine-II] (rev 74)
01:00.0 VGA compatible controller: VIA Technologies, Inc. VT8623 [Apollo CLE266] integrated CastleRo
ck graphics (rev 03)
root@xbmc:~#
```