


3ware RAID Stack?????LSI tty Log?????. ??????????Log:

LSI  **3DM2™** WIN-OOABFOSFB3N (Windows Server 2008 R2 Standard x64) Administrator logged in [Logout](#)

Summary Information Management Monitor 3DM2 Settings Help

Refresh **Controller Details** Select Controller Controller ID 0 (9690SA-8I)

Controller Details (Controller ID 0)

| | |
|---------------------|--------------------------------------|
| Model | 9690SA-8I |
| Serial # | L340503B8140772 |
| Firmware | FH9X 4.10.00.024 |
| Driver | 3.00.05.056 |
| BIOS | BE9X 4.08.00.004 |
| Boot Loader | BL9X 3.08.00.001 |
| Available Memory | 448 MB |
| Bus Type | PCIe |
| Bus Width | 8 lanes |
| Bus Speed | 2.5 Gbps/lane |
| Controller Phys | 8 |
| Connections | 5 of 128 |
| Drives | 5 of 128 |
| Units | 1 of 128 |
| Active Drives | 1 of 128 |
| Active Units | 1 of 32 |
| Max Drives per Unit | 32 |
| Error Log | [Download Error Log] |

????????????????????.

```
errorlog_0 - Notepad
File Edit Format View Help
### 3DM2 Version: 2.11.00.019
### Time Stamp: 16:20.59 21-Apr-2012
### Host Name: WIN-00ABF0SFB3N
### OS Version: Windows Server 2008 R2 standard x64 Edition Service Pack 1
### Driver Version: 3.00.05.056
### Controller ID: 0
### Model: 9690SA-8I
### Firmware: FH9X 4.10.00.024
### BIOS: BE9X 4.08.00.004
### Serial #: L340503B8140772
### Memory: 448 MB
### Bus Protocol: PCIE
### Bus width: 8 lanes
### Bus Speed: 2.5 Gbps/lane

### BEGIN Firmware Print Log
:10:10)
done. (count=6, bytes=119)
SETTINGS: Saving BIOS OPTION parameters ... done. (count=1, bytes=517)
ZeroUnit 0 command
Time : 15:10:30
Hard Reset Handler Started ...
FW Run Time = 00:02:57
Soft Resets = 0
Active IPRs = 0
Locked IPRs = 0
Actv Eh IPRs= 0
Active AOPs = 0
Active DOPs = 0
Active Cmds = 0
Data Blocks = 0
Parity Blks = 0
Response Queue:
Cur. HW FIFO= 0
SAS Amp|Pre[0] 0x0400|2c
```