

????

????	????/??	????	????	????	????	??DID	???
C2NET	??	G729,G711,G723	?	?? 99990001	?		
??	??	G711	?		?	??	
IPBB	??	G729,G711	?	(IPOX)0709803900	?		
Chief070	??	G729,G711	?	--	?	?? 070	????
GOGOTALK	??	—	?				???
A Voize	??	G729	?	??#9991000 ??#9000	?	??	???
Gizmo5	??	ilbc,G729,G711,GSM	?	1-747-474-3246	?		???
FWD-	??	G729,G711	?	613			???
Vbuzzer	??	G711	?	1-416-883-9633	?		
Voipstunt	??	G729,G711	?		?		
toCall	??	G729	?	1001	?		
ET263	??	G711	?		?		
iptel	??	none	?	3246	?		SIP Proxy
voiptalk	??	G729,G723	--	--	--	??	
IPComm	??	G711,G729	--	--	--	??	
sipgate	??	G.711	--	--	--	??(??30?)	
PennyTel	??	G723,G729	--	775,771	?	--	
Bluesip	??	G711	?	--	--	??	
Voxalot	??	G.729,G711	--	600	?		
SIPBroker	??		?		?		SIP Proxy
12voip	??	G729,G711,G726,G723	?		--		
Ekiga	??	G729,G711	?	500	?		
sip2sip	??	G711	?	3333	?		SIP Proxy

voipuser	??		?	0844 986 3246	?	??	
IdeaSIP	??		?		?		?????TollFree
Messagenet	??	G729,iLBC	?		?	???	

? [SIPBroker - EziDial](#) ????(Echo Test)

? iNum EchoTest: 883 5100 0000 0091

? ??????#[[#sectionAA|sectionAA]]

? ??-??

FET

????? SIP

Outgoing Settings

username=123456
 type=peer
 secret=thisispassword
 host=fsgw1.sparqnet.net
 fromuser=123456
 context=from-trunk
 insecure=port,invite

Incoming Settings

USER Context: ??

USER Details: ??

Register String: 123456:thisispassword@fsgw1.sparqnet.net

IPBB

?? - IPBB

Outgoing Settings

username=<sip_number>
 type=friend
 secret=<passowrd>
 qualify=yes
 insecure=port,invite (???????)
 host=msw1.mky.com
 disallow=all
 allow=g729
 context=from-trunk
 fromuser=<sip_number> (???????)

Incoming Settings

USER Context: ??

USER Details: ??

Register String:

<sip_number>:<password>@msw1.mky.com/<sip_number>

[?GO TO TOP?](#)

C2NET

???? - C2NET

Outgoing Settings

username=<sip_number>

type=friend

secret=<password>

port=7890

insecure=port,invite

host=210.202.244.130

qualify=yes

fromuser=<sip_number>

context=from-trunk

Incoming Settings

USER Context: ??

USER Details: ??

Register String:

<sip_number>:<password>@210.202.244.130:7890/<sip_number>

[?GO TO TOP?](#)

Chief070

???? (???2013/06???????????????? LoadBalance SIP Client ????)

Outgoing Settings

username=<sip_number>

secret=<password>

host=202.133.231.17

type=peer

Incoming Settings

USER Context: ??

USER Details: ??

Register String:

<sip_number>:<password>@202.133.231.17/<sip_number>

?? Chief070 ? outbound proxy ?????????????????????? [Loadbalance ? SIP Provider?](#)

[?GO TO TOP?](#)

? ??

Gizmo5

Outgoing Settings

username=<sip_number>
type=peer
secret=<password>
qualify=yes
insecure=very
host=proxy01.sipphone.com
fromuser=<sip_number>
fromdomain=proxy01.sipphone.com
dtmfmode=rfc2833
disallow=all
canreinvite=no
authuser=<sip_number>
allow=g729&ulaw&gsm
context=from-trunk

Incoming Settings

USER Context: ??
USER Details: ??

Register String:

<sip_number>:<password>@proxy01.sipphone.com/<sip_number>

[?GO TO TOP?](#)

Vbuzzer

Echo-Test Number(????)?1-416-883-9633

Outgoing Settings:

username=<user_name>
useragent=VBuzzer/1.1.0.9
user=<user_name>
type=peer
secret=<password>
qualify=yes
port=80
insecure=very
host=vbuzzer.com
hidecallerid=yes

fromuser=<user_name>
fromdomain=vbuzzer.com
dtmfmode=rfc2833
dtmf=rfc2833
disallow=all
canreinvite=no
authname=<user_name>
allow=ulaw&gsm

Incoming Settings:

username=<user_name>
useragent=vbuzzer/1.1.1.0
user=<user_name>
type=user
secret=<password>
port=80
insecure=very
host=vbuzzer.com
fromuser=<user_name>
fromdomain=vbuzzer.com
canreinvite=no
authname=<user_name>
context=from-trunk

[?GO TO TOP?](#)

Voipstunt

Outgoing Settings:

username=<user_name>
type=peer
secret=<password>
insecure=very
host=sip.voipstunt.com
disallow=all
canreinvite=no
allow=g729

[?GO TO TOP?](#)

toCall

Outgoing Settings:

host=sip.tocall.cn
username=<sip_number>
secret=<password>
type=peer

iptel

Outgoing Settings:

host=iptel.org
username=<sip_number>
secret=<password>
type=friend
fromdomain=iptel.org
fromuser=<sip_number>
insecure=port,invite
context=from-trunk
disallow=all
allow=ulaw

Incoming Setting: ??

USER Details: ??

Register String:

<sip_number>:<password>@iptel.org/<sip_number>

[?GO TO TOP?](#)

voiptalk

Outgoing Settings:

host=voiptalk.org
username=<sip_number>
secret=<password>
type=peer
insecure=very
context=from-trunk

Register String:

<sip_number>:<password>@voiptalk.org/<DID_number>

[?GO TO TOP?](#)

IPComm

IP Communications - Free DID in US

Outgoing Settings:

Trunk Name: IPC

PEER Details: ??

Incoming Settings:

USER Context: <DID_Number> ;????? 1

USER Details:

allow=g729

host=64.154.41.100
insecure=port,invite
type=peer
context=from-trunk
nat=yes
dtmfmode=rfc2833

[?GO TO TOP?](#)

siggate

Free DID in US

Outgoing Settings:

type=peer
username=<sip_username>
fromuser=<sip_username>
defaultuser=<sip_username>
secret=<sip_password>
context=from-trunk
host=sipgate.com
fromdomain=sipgate.com
outboundproxy=proxy.live.sipgate.com
insecure=invite
canreinvite=no
nat=no
disallow=all
allow=ulaw&alaw
qualify=yes
dtmfmode=rfc2833

Incoming Setting: ??

USER Details: ??

Register String:

<sip_username>:<sip_password>@sipgate.com/<DID_number>

[?GO TO TOP?](#)

PennyTel

Outgoing Settings:

Trunk Name: pennytel

PEER Details:

username=<sip_number>
type=peer
secret=<password>
insecure=very
host=sip.pennytel.com

disallow=all
canreinvite=no
canredirect=no
allow=g729&g723
context=from-trunk

Incoming Settings:
USER Context: <blank>
USER Details: <blank>

Register String:
<sip_number>:<password>@sip.pennytel.com/<sip_number>

[?GO TO TOP?](#)

Bluesip

Free DID in German

Outgoing Settings:
Trunk Name: bluesip
PEER Details:

host=bluesip.net
type=friend
username=<bluesip/sip_username>
fromuser=<sip_username>
fromdomain=bluesip.net
secret=<password>
qualify=yes
canreinvite=no
nat=no
disallow=all
allow=ulaw&alaw
insecure=very
auth=md5,plaintext
context=from-trunk

Incoming Settings:
USER Context: <??>
USER Details: <??>

Register String:
<bluesip/sip_username>:<password>@bluesip.net/<DID_number>

[?GO TO TOP?](#)

Voxalot

Outgoing Settings:
Trunk Name: voxalot

PEER Details:

host=us.voxalot.com
username=<sip_number>
fromuser=<sip_number>
secret=<sip_password>
fromdomain=voxalot.com
nat=yes
insecure=very
qualify=yes
canreinvite=yes
dtmfmode=auto
disallow=all
allow=g729&ulaw&alaw
type=peer
context=from-trunk

Incoming Settings:

USER Context: <??>
USER Details: <??>

Register String:

<sip_number>:<sip_password>@us.voxalot.com/<sip_number>

[?GO TO TOP?](#)

SIPBroker

????,??? SIP URI ???? provider,?? 1234?iptel.org
sip_user=1234
sip_domain=iptel.org

Outgoing Settings:

Trunk Name: sipbroker
PEER Details:

type=peer
port=5060
host=sipbroker.com
fromuser=<sip_user>
fromdomain=<sip_domain>
canreinvite=yes

Incoming Settings:

USER Context: <??>
USER Details: <??>

Register String:<??>

[?GO TO TOP?](#)

12voip

Outgoing Settings:

Trunk Name: 12voip

PEER Details:

```
host=sip.12voip.com
username=<sip_user>
secret=<sip_pass>
type=peer
disallow=all
allow=g729
qualify=yes
```

Incoming Settings:

USER Context: <??>

USER Details: <??>

Register String:<??>

[?GO TO TOP?](#)

Ekiga

http://wiki.ekiga.org/index.php/Main_Page

Outgoing Settings:

Trunk Name: ekiga

PEER Details:

```
type=friend
username=<sip_number>
secret=<sip_password>
host=ekiga.net
canreinvite=no
qualify=300
insecure=port,invite
context=from-trunk
```

Incoming Settings:

USER Context: <??>

USER Details: <??>

Register String:

<sip_number>:<sip_password>@ekiga.net/<sip_number>

[?GO TO TOP?](#)

sip2sip

<http://wiki.sip2sip.info/wiki/SipDev...sk#AsteriskPBX>

??sip.conf ?? srvlookup=yes (??)

?? sip2sip ? outbound proxy ? load balancing ?????????????????????????? [Loadbalance ? SIP Provider?](#)

[?GO TO TOP?](#)

voipuser

Outgoing Settings:

Trunk Name: voipuser

PEER Details:

host=sip.voipuser.org
username=<sip_username>
secret=<sip_password>
type=peer
qualify=yes
insecure=port,invite
context=from-trunk

Incoming Settings:

USER Context: <??>

USER Details: <??>

Register String:

<sip_username>:<sip_password>@sip.voipuser.org/<DID_number>

[?GO TO TOP?](#)

IdeaSIP

Outgoing Settings:

Trunk Name: ideasip

PEER Details:

host=proxy.ideasip.com
fromdomain=proxy.ideasip.com
username=<sip_username>
secret=<sip_password>
type=friend
insecure=port,invite
context=from-trunk

Incoming Settings:

USER Context: <??>

USER Details: <??>

Register String:

<sip_username>:<sip_password>@proxy.ideasip.com/<SIP_number>

MessageNet

Outgoing Settings:

Trunk Name: messagenet

PEER Details:

type=peer
auth=md5
username=<sip_username>
fromuser=<sip_username>
secret=<sip_password>
host=sip.messagenet.it
port=5061
qualify=yes
insecure=port,invite
context=from-trunk
disallow=all
allow=g729

Incoming Settings:

USER Context: <??>

USER Details: <??>

Register String:

<sip_username>:<sip_password>@sip.messagenet.it:5061/<DID_Number>