

????

????	????/??	????	????	????	????	??DID	???
<a href="#">C2NET</a>	<a href="#">??</a>	G729,G711,G723	?	?? 99990001	?		
??	??	G711	?		?	??	
<a href="#">IPBB</a>	<a href="#">??</a>	G729,G711	?	(IPOX)0709803900	?		
<a href="#">Chief070</a>	<a href="#">??</a>	G729,G711	?	--	?	?? 070	????
<a href="#">GOGOTALK</a>	??	—	?				???
<a href="#">A Voize</a>	<a href="#">??</a>	G729	?	??#9991000 ??#9000	?	??	???
<a href="#">Gizmo5</a>	<a href="#">??</a>	ilbc,G729,G711,GSM	?	1-747-474-3246	?		???
<a href="#">FWD-</a>	<a href="#">??</a>	G729,G711	?	613			???
<a href="#">Vbuzzer</a>	??	G711	?	1-416-883-9633	?		
<a href="#">Voipstunt</a>	<a href="#">??</a>	G729,G711	?		?		
<a href="#">toCall</a>	<a href="#">??</a>	G729	?	1001	?		
<a href="#">ET263</a>	<a href="#">??</a>	G711	?		?		
<a href="#">iptel</a>	<a href="#">??</a>	none	?	3246	?		SIP Proxy
<a href="#">voiptalk</a>	<a href="#">??</a>	G729,G723	--	--	--	??	
<a href="#">IPComm</a>	<a href="#">??</a>	G711,G729	--	--	--	??	
<a href="#">sipgate</a>	<a href="#">??</a>	G.711	--	--	--	??(??30?)	
<a href="#">PennyTel</a>	<a href="#">??</a>	G723,G729	--	775,771	?	--	
<a href="#">Bluesip</a>	<a href="#">??</a>	G711	?	--	--	??	
<a href="#">Voxalot</a>	<a href="#">??</a>	G.729,G711	--	600	?		
<a href="#">SIPBroker</a>	<a href="#">??</a>		?		?		SIP Proxy
<a href="#">12voip</a>	<a href="#">??</a>	G729,G711,G726,G723	?		--		
<a href="#">Ekiga</a>	<a href="#">??</a>	G729,G711	?	500	?		
<a href="#">sip2sip</a>	<a href="#">??</a>	G711	?	3333	?		SIP Proxy

<a href="#">voipuser</a>	??		?	0844 986 3246	?	??	
<a href="#">IdeaSIP</a>	??		?		?		?????TollFree
<a href="#">Messagenet</a>	??	G729,iLBC	?		?	???	

? [SIPBroker - EziDial](#) ???? (Echo Test)

? iNum EchoTest: 883 5100 0000 0091

? ??????#[[#sectionAA|sectionAA]]

? ??-??

**FET**

????? SIP

Outgoing Settings

username=123456  
 type=peer  
 secret=thisispassword  
 host=fsgw1.sparqnet.net  
 fromuser=123456  
 context=from-trunk  
 insecure=port,invite

Incoming Settings

USER Context: ??

USER Details: ??

Register String: 123456:thisispassword@fsgw1.sparqnet.net

**IPBB**

?? - IPBB

Outgoing Settings

username=<sip\_number>  
 type=friend  
 secret=<passowrd>  
 qualify=yes  
 insecure=port,invite (???????)  
 host=msw1.mky.com  
 disallow=all  
 allow=g729  
 context=from-trunk  
 fromuser=<sip\_number> (???????)

Incoming Settings

USER Context: ??

USER Details: ??

Register String:

<sip\_number>:<password>@msw1.mky.com/<sip\_number>

[?GO TO TOP?](#)

### **C2NET**

???? - C2NET

Outgoing Settings

username=<sip\_number>

type=friend

secret=<password>

port=7890

insecure=port,invite

host=210.202.244.130

qualify=yes

fromuser=<sip\_number>

context=from-trunk

Incoming Settings

USER Context: ??

USER Details: ??

Register String:

<sip\_number>:<password>@210.202.244.130:7890/<sip\_number>

[?GO TO TOP?](#)

### **Chief070**

???? (???2013/06???????????????? LoadBalance SIP Client ????)

Outgoing Settings

username=<sip\_number>

secret=<password>

host=202.133.231.17

type=peer

Incoming Settings

USER Context: ??

USER Details: ??

Register String:

<sip\_number>:<password>@202.133.231.17/<sip\_number>

?? Chief070 ? outbound proxy ?????????????????????? [Loadbalance ? SIP Provider?](#)

[?GO TO TOP?](#)

---

? ??

**Gizmo5**

Outgoing Settings

username=<sip\_number>  
type=peer  
secret=<password>  
qualify=yes  
insecure=very  
host=proxy01.sipphone.com  
fromuser=<sip\_number>  
fromdomain=proxy01.sipphone.com  
dtmfmode=rfc2833  
disallow=all  
canreinvite=no  
authuser=<sip\_number>  
allow=g729&ulaw&gsm  
context=from-trunk

Incoming Settings

USER Context: ??  
USER Details: ??

Register String:

<sip\_number>:<password>@proxy01.sipphone.com/<sip\_number>

[?GO TO TOP?](#)

**Vbuzzer**

Echo-Test Number(????)?1-416-883-9633

Outgoing Settings:

username=<user\_name>  
useragent=VBuzzer/1.1.0.9  
user=<user\_name>  
type=peer  
secret=<password>  
qualify=yes  
port=80  
insecure=very  
host=vbuzzer.com  
hidecallerid=yes

fromuser=<user\_name>  
fromdomain=vbuzzer.com  
dtmfmode=rfc2833  
dtmf=rfc2833  
disallow=all  
canreinvite=no  
authname=<user\_name>  
allow=ulaw&gsm

Incoming Settings:

username=<user\_name>  
useragent=vbuzzer/1.1.1.0  
user=<user\_name>  
type=user  
secret=<password>  
port=80  
insecure=very  
host=vbuzzer.com  
fromuser=<user\_name>  
fromdomain=vbuzzer.com  
canreinvite=no  
authname=<user\_name>  
context=from-trunk

[?GO TO TOP?](#)

**Voipstunt**

Outgoing Settings:

username=<user\_name>  
type=peer  
secret=<password>  
insecure=very  
host=sip.voipstunt.com  
disallow=all  
canreinvite=no  
allow=g729

[?GO TO TOP?](#)

**toCall**

Outgoing Settings:

host=sip.tocall.cn  
username=<sip\_number>  
secret=<password>  
type=peer



**iptel**

Outgoing Settings:

host=iptel.org  
username=<sip\_number>  
secret=<password>  
type=friend  
fromdomain=iptel.org  
fromuser=<sip\_number>  
insecure=port,invite  
context=from-trunk  
disallow=all  
allow=ulaw

Incoming Setting: ??

USER Details: ??

Register String:

<sip\_number>:<password>@iptel.org/<sip\_number>

[?GO TO TOP?](#)

**voiptalk**

Outgoing Settings:

host=voiptalk.org  
username=<sip\_number>  
secret=<password>  
type=peer  
insecure=very  
context=from-trunk

Register String:

<sip\_number>:<password>@voiptalk.org/<DID\_number>

[?GO TO TOP?](#)

**IPComm**

IP Communications - Free DID in US

Outgoing Settings:

Trunk Name: IPC

PEER Details: ??

Incoming Settings:

USER Context: <DID\_Number> ;????? 1

USER Details:

allow=g729

host=64.154.41.100  
insecure=port,invite  
type=peer  
context=from-trunk  
nat=yes  
dtmfmode=rfc2833

[?GO TO TOP?](#)

**siggate**

Free DID in US

Outgoing Settings:

type=peer  
username=<sip\_username>  
fromuser=<sip\_username>  
defaultuser=<sip\_username>  
secret=<sip\_password>  
context=from-trunk  
host=sipgate.com  
fromdomain=sipgate.com  
outboundproxy=proxy.live.sipgate.com  
insecure=invite  
canreinvite=no  
nat=no  
disallow=all  
allow=ulaw&alaw  
qualify=yes  
dtmfmode=rfc2833

Incoming Setting: ??

USER Details: ??

Register String:

<sip\_username>:<sip\_password>@sipgate.com/<DID\_number>

[?GO TO TOP?](#)

**PennyTel**

Outgoing Settings:

Trunk Name: pennytel

PEER Details:

username=<sip\_number>  
type=peer  
secret=<password>  
insecure=very  
host=sip.pennytel.com



disallow=all  
canreinvite=no  
canredirect=no  
allow=g729&g723  
context=from-trunk

Incoming Settings:  
USER Context: <blank>  
USER Details: <blank>

Register String:  
<sip\_number>:<password>@sip.pennytel.com/<sip\_number>

[?GO TO TOP?](#)

### **Bluesip**

Free DID in German

Outgoing Settings:  
Trunk Name: bluesip  
PEER Details:

host=bluesip.net  
type=friend  
username=<bluesip/sip\_username>  
fromuser=<sip\_username>  
fromdomain=bluesip.net  
secret=<password>  
qualify=yes  
canreinvite=no  
nat=no  
disallow=all  
allow=ulaw&alaw  
insecure=very  
auth=md5,plaintext  
context=from-trunk

Incoming Settings:  
USER Context: <??>  
USER Details: <??>

Register String:  
<bluesip/sip\_username>:<password>@bluesip.net/<DID\_number>

[?GO TO TOP?](#)

### **Voxalot**

Outgoing Settings:  
Trunk Name: voxalot

PEER Details:

host=us.voxalot.com  
username=<sip\_number>  
fromuser=<sip\_number>  
secret=<sip\_password>  
fromdomain=voxalot.com  
nat=yes  
insecure=very  
qualify=yes  
canreinvite=yes  
dtmfmode=auto  
disallow=all  
allow=g729&ulaw&alaw  
type=peer  
context=from-trunk

Incoming Settings:

USER Context: <??>  
USER Details: <??>

Register String:

<sip\_number>:<sip\_password>@us.voxalot.com/<sip\_number>

[?GO TO TOP?](#)

**SIPBroker**

????,??? SIP URI ??? provider,?? 1234?iptel.org

sip\_user=1234  
sip\_domain=iptel.org

Outgoing Settings:

Trunk Name: sipbroker

PEER Details:

type=peer  
port=5060  
host=sipbroker.com  
fromuser=<sip\_user>  
fromdomain=<sip\_domain>  
canreinvite=yes

Incoming Settings:

USER Context: <??>  
USER Details: <??>

Register String:<??>

[?GO TO TOP?](#)

### 12voip

Outgoing Settings:

Trunk Name: 12voip

PEER Details:

```
host=sip.12voip.com
username=<sip_user>
secret=<sip_pass>
type=peer
disallow=all
allow=g729
qualify=yes
```

Incoming Settings:

USER Context: <??>

USER Details: <??>

Register String:<??>

[?GO TO TOP?](#)

### Ekiga

[http://wiki.ekiga.org/index.php/Main\\_Page](http://wiki.ekiga.org/index.php/Main_Page)

Outgoing Settings:

Trunk Name: ekiga

PEER Details:

```
type=friend
username=<sip_number>
secret=<sip_password>
host=ekiga.net
canreinvite=no
qualify=300
insecure=port,invite
context=from-trunk
```

Incoming Settings:

USER Context: <??>

USER Details: <??>

Register String:

<sip\_number>:<sip\_password>@ekiga.net/<sip\_number>

[?GO TO TOP?](#)

**sip2sip**

<http://wiki.sip2sip.info/wiki/SipDev...sk#AsteriskPBX>

??sip.conf ?? srvlookup=yes (??)

?? sip2sip ? outbound proxy ? load balancing ?????????????????????????? [Loadbalance ? SIP Provider?](#)

[?GO TO TOP?](#)

**voipuser**

Outgoing Settings:

Trunk Name: voipuser

PEER Details:

host=sip.voipuser.org  
username=<sip\_username>  
secret=<sip\_password>  
type=peer  
qualify=yes  
insecure=port,invite  
context=from-trunk

Incoming Settings:

USER Context: <??>

USER Details: <??>

Register String:

<sip\_username>:<sip\_password>@sip.voipuser.org/<DID\_number>

[?GO TO TOP?](#)

**IdeaSIP**

Outgoing Settings:

Trunk Name: ideasip

PEER Details:

host=proxy.ideasip.com  
fromdomain=proxy.ideasip.com  
username=<sip\_username>  
secret=<sip\_password>  
type=friend  
insecure=port,invite  
context=from-trunk

Incoming Settings:

USER Context: <??>

USER Details: <??>

Register String:

<sip\_username>:<sip\_password>@proxy.ideasip.com/<SIP\_number>

**MessageNet**

Outgoing Settings:

Trunk Name: messagenet

PEER Details:

type=peer  
auth=md5  
username=<sip\_username>  
fromuser=<sip\_username>  
secret=<sip\_password>  
host=sip.messagenet.it  
port=5061  
qualify=yes  
insecure=port,invite  
context=from-trunk  
disallow=all  
allow=g729

Incoming Settings:

USER Context: <??>

USER Details: <??>

Register String:

<sip\_username>:<sip\_password>@sip.messagenet.it:5061/<DID\_Number>