

????

- CentOS 6
- SNMPTT 1.4

?? Perl Module

?: <http://repoforge.org/use/>

```
#> rpm -ivh rpmforge-release-0.5.3-1.el6.rf.x86_64.rpm
#> yum install perl-Config-IniFiles
```

???? SNMPTT

?: <http://snmptt.sourceforge.net/downloads.shtml>

```
#> tar xzf snmptt_1.4.tgz
#> cd snmptt_1.4/

#> cp ./snmptt /usr/sbin/
#> chmod a+x /usr/sbin/snmptt

#> cp ./snmptthandler /usr/sbin/
#> chmod a+x /usr/sbin/snmptthandler

#> cp ./snmpttconvert /usr/sbin/
#> chmod a+x /usr/sbin/snmpttconvert

#> cp ./snmpttconvertmib /usr/sbin/
#> chmod a+x /usr/sbin/snmpttconvertmib

#> cp ./snmptt.ini /etc/snmp/
#> cp examples/snmptt.conf.generic /etc/snmp/snmptt.conf
#> mkdir /var/log/snmptt
#> vi /etc/snmp/snmpttrapd.conf

traphandle default /usr/sbin/snmptthandler

#> mkdir /var/spool/snmptt/
```

??????

```
#> cp snmptt-init.d /etc/rc.d/init.d/snmptt
#> chmod 0755 /etc/rc.d/init.d/snmptt
#> chkconfig --add snmptt
#> chkconfig snmptt on
#> service snmptt start
```

?? logrotate

```
#> cp snmptt.logrotate /etc/logrotate.d/snmptt
```

?? snmptrapd

```
#> vi /etc/sysconfig/snmptrapd
```

```
OPTIONS="-On -Lsd -p /var/run/snmptrapd.pid"
```

NOTE: The -On is recommended. This will make snmptrapd pass OIDs in numeric form and prevent SNMPTT from having to translate the symbolic name to numerical form. If the UCD-SNMP / Net-SNMP Perl module is not installed, then you MUST use the -On switch. Depending on the version of UCD-SNMP / Net-SNMP, some symbolic names may not translate correctly. See the FAQ for more info.

?? snmptrapd ??

```
#> service snmptrapd start
```

```
#> chkconfig snmptrapd on
```