

CentOS 5/6

?????)

/etc/snmp/snmpd.conf:

```
# sec.name source      community
#com2sec notConfigUser default    public
# added by alang
com2sec notConfigUser default    YOURCOMPANY

# groupName securityModel securityName
group notConfigGroup v1      notConfigUser
group notConfigGroup v2c     notConfigUser

# Make at least snmpwalk -v 1 localhost -c public system fast again.
# name      incl/excl subtree  mask(optional)
view systemview included .1.3.6.1.2.1.1
view systemview included .1.3.6.1.2.1.25.1.1
#added by alang
view all     included .1

####
# Finally, grant the group read-only access to the systemview view.

# group      context sec.model sec.level prefix read  write notif
#access notConfigGroup ""    any    noauth  exact systemview none none
# added by alang
access notConfigGroup ""    any    noauth  exact all none none
```

? Cacti ???)

Cacti Admin > Device > Add

- Description: <??>
- Hostname: Linux ??? IP
- Host Template: Linux
- Number of Collection Threads: 1 Thread(default)
- Disable Host: ??
- Monitor Host: ??
- Downed Device Detection: None
- SNMP Version: Version 2
- SNMP Community: YOURCOMPANY
- SNMP Port: 161
- SNMP Timeout: 500
- Maximum OID's Per Get Request: 100