

Cmd	Description
service fail2ban restart	restart fail2ban service (after edit configuration)
fail2ban-client reload	restart fail2ban client
fail2ban-client status	get list activated jail
fail2ban-client status <JAIL> example: fail2ban-client status wplogin example: fail2ban-client status sshd	get <JAIL> status (the number of unsuccessful attempts and the list of banned IPs)
fail2ban-regex /var/lib/docker/ containers/<CONTAINERID>/<CONTAINERID>- json.log /etc/fail2ban/filter.d/wplogin.conf	test regex wplogin
fail2ban-regex /var/log/auth.log /etc/ fail2ban/filter.d/sshd.conf	test regex sshd
fail2ban-regex "line" "failregex"	test regex
fail2ban-client set <JAIL-NAME> unbanip <IP- ADDRESS>	manually unban IP
fail2ban-client set <JAIL-NAME> banip <IP- ADDRESS>	manually Ban IP
tail -f /var/log/fail2ban.log	view fail2ban logs
iptables -L -line-numbers	list IP blocked with line numbers
iptables -D <Jail-Name> -s <IP-ADDRESS> -j DROP Example: Jail-Name =f2b-wplogin Jail-Name =f2b-sshd	Unban IP
fail2ban-server -b	start fail2ban server
docker inspect --format='{{.LogPath}}' \$INSTANCE_ID	return instance log file path