

Cmd	Description
<code>service fail2ban restart</code>	restart fail2ban service (after edit configuration)
<code>fail2ban-client reload</code>	restart fail2ban client
<code>fail2ban-client status</code>	get list activated jail
<code>fail2ban-client status &lt;JAIL&gt;</code> example: <code>fail2ban-client status wplogin</code> example: <code>fail2ban-client status sshd</code>	get <JAIL> status (the number of unsuccessful attempts and the list of banned IPs)
<code>fail2ban-regex /var/lib/docker/containers/&lt;CONTAINERID&gt;/&lt;CONTAINERID&gt;-json.log /etc/fail2ban/filter.d/wplogin.conf</code>	test regex wplogin
<code>fail2ban-regex /var/log/auth.log /etc/fail2ban/filter.d/sshd.conf</code>	test regex sshd
<code>fail2ban-regex "line" "failregex"</code>	test regex
<code>fail2ban-client set &lt;JAIL-NAME&gt; unbanip &lt;IP-ADDRESS&gt;</code>	manually unban IP
<code>fail2ban-client set &lt;JAIL-NAME&gt; banip &lt;IP-ADDRESS&gt;</code>	manually Ban IP
<code>tail -f /var/log/fail2ban.log</code>	view fail2ban logs
<code>iptables -L -line-numbers</code>	list IP blocked with line numbers
<code>iptables -D &lt;Jail-Name&gt; -s &lt;IP-ADDRESS&gt; -j DROP</code> Example: <code>Jail-Name =f2b-wplogin</code> <code>Jail-Name =f2b-sshd</code>	Unban IP
<code>fail2ban-server -b</code>	start fail2ban server
<code>docker inspect --format='{{.LogPath}}' \$INSTANCE_ID</code>	return instance log file path