

????

- iSCSI Storage: NetApp FAS8200
- Linux OS: CentOS 7
- Server H/W: HP DL380 Gen10
- iSCSI ?????: 10G SFP ?????? x 2

?????

????? nmtui ?????????? IP ? Mask

??: ?????????? Bonding?

?? iSCSI

?? iscsi ??

yum install iscsi-initiator-utils

?? iscsid.conf

vi /etc/iscsi/iscsid.conf

?? timeout

```
#node.session.timeout = 120
node.session.replacement_timeout = 5
```

?? node ?? Login

node.startup = automatic

?? initiator name

vi /etc/iscsi/initiatorname.iscsi

?????????

iqn.<year-to-date>.<your-domain>.<your-hostname>:redhat-disk  
??

InitiatorName=iqn.2019-02.mycompany.bdb7-a:redhat-disk

initiator name ??? Storage ??????

??? Host ??????????

**?? multipath ? netapp\_linux\_unified\_host\_utilities**

```
yum install device-mapper-multipath
yum install libhbaapi
rpm -ivh netapp_linux_unified_host_utilities-7-1.x86_64.rpm
```

?????? libhbaapi??? sanlun ??????

**?? iSCSI storage**

???????

```
iscsiadm -m iface -I iscsi_ens2f0 --op=new
iscsiadm -m iface -I iscsi_ens3f0 --op=new
```

Discovery for the storage

```
iscsiadm -m discovery -t sendtargets -p <ip-to-iscsi-storage>:3260
```

?? NetApp storage ????? iSCSI IPs????????? IP ?????????????? IP?

```
[root@bdb7-b RPMs]# iscsiadm -m discovery -t sendtargets -p 10.18.104.32:3260
10.18.104.32:3260,1038 iqn.1992-08.com.netapp:sn.58042162340f11e9892700a098e3ab45:vs.16
10.18.104.34:3260,1040 iqn.1992-08.com.netapp:sn.58042162340f11e9892700a098e3ab45:vs.16
10.18.104.33:3260,1039 iqn.1992-08.com.netapp:sn.58042162340f11e9892700a098e3ab45:vs.16
10.18.104.31:3260,1037 iqn.1992-08.com.netapp:sn.58042162340f11e9892700a098e3ab45:vs.16
10.18.104.32:3260,1038 iqn.1992-08.com.netapp:sn.58042162340f11e9892700a098e3ab45:vs.16
10.18.104.34:3260,1040 iqn.1992-08.com.netapp:sn.58042162340f11e9892700a098e3ab45:vs.16
10.18.104.33:3260,1039 iqn.1992-08.com.netapp:sn.58042162340f11e9892700a098e3ab45:vs.16
10.18.104.31:3260,1037 iqn.1992-08.com.netapp:sn.58042162340f11e9892700a098e3ab45:vs.16
```

Login nodes

```
iscsiadm -m node -l all
```

?????????????

```
[root@bdb7-b RPMs]# iscsiadm -m node -l all
Logging in to [iface: iscsi_ens2f0, target:
iqn.1992-08.com.netapp:sn.58042162340f11e9892700a098e3ab45:vs.16, portal: 10.18.104.32,3260]
(multiple)
Logging in to [iface: iscsi_ens3f0, target:
iqn.1992-08.com.netapp:sn.58042162340f11e9892700a098e3ab45:vs.16, portal: 10.18.104.32,3260]
(multiple)
Logging in to [iface: iscsi_ens2f0, target:
iqn.1992-08.com.netapp:sn.58042162340f11e9892700a098e3ab45:vs.16, portal: 10.18.104.34,3260]
(multiple)
Logging in to [iface: iscsi_ens3f0, target:
iqn.1992-08.com.netapp:sn.58042162340f11e9892700a098e3ab45:vs.16, portal: 10.18.104.34,3260]
```

(multiple)

Logging in to [iface: iscsi\_ens2f0, target:

iqn.1992-08.com.netapp:sn.58042162340f11e9892700a098e3ab45:vs.16, portal: 10.18.104.33,3260]

(multiple)

Logging in to [iface: iscsi\_ens3f0, target:

iqn.1992-08.com.netapp:sn.58042162340f11e9892700a098e3ab45:vs.16, portal: 10.18.104.33,3260]

(multiple)

Logging in to [iface: iscsi\_ens2f0, target:

iqn.1992-08.com.netapp:sn.58042162340f11e9892700a098e3ab45:vs.16, portal: 10.18.104.31,3260]

(multiple)

Logging in to [iface: iscsi\_ens3f0, target:

iqn.1992-08.com.netapp:sn.58042162340f11e9892700a098e3ab45:vs.16, portal: 10.18.104.31,3260]

(multiple)

Login to [iface: iscsi\_ens2f0, target:

iqn.1992-08.com.netapp:sn.58042162340f11e9892700a098e3ab45:vs.16, portal: 10.18.104.32,3260]

successful.

Login to [iface: iscsi\_ens3f0, target:

iqn.1992-08.com.netapp:sn.58042162340f11e9892700a098e3ab45:vs.16, portal: 10.18.104.32,3260]

successful.

Login to [iface: iscsi\_ens2f0, target:

iqn.1992-08.com.netapp:sn.58042162340f11e9892700a098e3ab45:vs.16, portal: 10.18.104.34,3260]

successful.

Login to [iface: iscsi\_ens3f0, target:

iqn.1992-08.com.netapp:sn.58042162340f11e9892700a098e3ab45:vs.16, portal: 10.18.104.34,3260]

successful.

Login to [iface: iscsi\_ens2f0, target:

iqn.1992-08.com.netapp:sn.58042162340f11e9892700a098e3ab45:vs.16, portal: 10.18.104.33,3260]

successful.

Login to [iface: iscsi\_ens3f0, target:

iqn.1992-08.com.netapp:sn.58042162340f11e9892700a098e3ab45:vs.16, portal: 10.18.104.33,3260]

successful.

Login to [iface: iscsi\_ens2f0, target:

iqn.1992-08.com.netapp:sn.58042162340f11e9892700a098e3ab45:vs.16, portal: 10.18.104.31,3260]

successful.

Login to [iface: iscsi\_ens3f0, target:

iqn.1992-08.com.netapp:sn.58042162340f11e9892700a098e3ab45:vs.16, portal: 10.18.104.31,3260]

successful.

?? sanlun ?? LUN Disks

sanlun lun show

controller(7mode/E-Series)/ vserver(cDOT/FlashRay)	lun-pathname	device filename	host adapter	lun protocol	size
TPEDBISCSISVM01 500.1g cDOT	/vol/BDB7_B_4_vol/BDB7_B_4	/dev/sdag	host19	iSCSI	

TPEDBISCSISVM01	/vol/BDB7_B_4_vol/BDB7_B_4	/dev/sdaf	host20	iSCSI
500.1g cDOT				
TPEDBISCSISVM01	/vol/BDB7_B_4_vol/BDB7_B_4	/dev/sdae	host17	iSCSI
500.1g cDOT				
TPEDBISCSISVM01	/vol/BDB7_B_4_vol/BDB7_B_4	/dev/sdad	host18	iSCSI
500.1g cDOT				
TPEDBISCSISVM01	/vol/BDB7_B_4_vol/BDB7_B_4	/dev/sdac	host16	iSCSI
500.1g cDOT				
TPEDBISCSISVM01	/vol/BDB7_B_4_vol/BDB7_B_4	/dev/sdab	host15	iSCSI
500.1g cDOT				
TPEDBISCSISVM01	/vol/BDB7_B_3_vol/BDB7_B_3	/dev/sdz	host20	iSCSI
500.1g cDOT				
TPEDBISCSISVM01	/vol/BDB7_B_3_vol/BDB7_B_3	/dev/sdaa	host19	iSCSI
500.1g cDOT				
TPEDBISCSISVM01	/vol/BDB7_B_4_vol/BDB7_B_4	/dev/sdy	host14	iSCSI
500.1g cDOT				
TPEDBISCSISVM01	/vol/BDB7_B_3_vol/BDB7_B_3	/dev/sdx	host18	iSCSI
500.1g cDOT				
TPEDBISCSISVM01	/vol/BDB7_B_3_vol/BDB7_B_3	/dev/sdw	host17	iSCSI
500.1g cDOT				
TPEDBISCSISVM01	/vol/BDB7_B_3_vol/BDB7_B_3	/dev/sdt	host16	iSCSI
cDOT				500.1g
TPEDBISCSISVM01	/vol/BDB7_B_3_vol/BDB7_B_3	/dev/sdu	host15	iSCSI
500.1g cDOT				
...				

**?? multipath**

????????????? multipath.conf

mpathconf --enable --with\_multipathd y

?? device alias name ? LUN WWID ???

???? RedHat 7.6 ? multipathd ?????? user\_friendly\_names yes  
 ??? NetApp ? LUN disks ?????? mpath X ?????????? WWID?????????

????????????????? WWID ???

?? /etc/multipath.conf

?????????????

...

```

multipaths {
  multipath {
    wwid 3600a0980383136312d3f4e387455564b
    alias mpath1
  }
}

```

```

multipath {
    wwid 3600a0980383136312d3f4e387455564c
    alias mpath2
}
multipath {
    wwid 3600a0980383136312d3f4e387455564d
    alias mpath3
}
multipath {
    wwid 3600a0980383136312d3f4e387455564e
    alias mpath4
}
}

```

wwid ????? multipath -l ??

alias ??????????LUN disks???????? sanlun lun show ??

?????

systemctl reload multipathd

?? multipath -l?????? WWID ? Alias Name

```

mpath2 (3600a0980383136312d3f4e387455564c) dm-5 NETAPP ,LUN C-Mode
size=500G features='4 queue_if_no_path pg_init_retries 50 retain_attached_hw_handle'
hw_handler='1 alua' wp=rw
`-- policy='service-time 0' prio=0 status=active
  |- 12:0:0:1 sdo 8:224 active undef running
  |- 13:0:0:1 sds 65:32 active undef running
  |- 15:0:0:1 sdaa 65:160 active undef running
  `- 16:0:0:1 sdae 65:224 active undef running
`-- policy='service-time 0' prio=0 status=enabled
  |- 10:0:0:1 sdg 8:96 active undef running
  |- 11:0:0:1 sdk 8:160 active undef running
  |- 14:0:0:1 sdw 65:96 active undef running
  `- 9:0:0:1 sdc 8:32 active undef running

```

???? iSCSI LUNs

?????????????????????????

?? /etc/fstab  
? iSCSI disk ????? \_netdev

#device	mount point	FS	Options	Backup	fsck
/dev/myvg/mylv	/mydisk	xfs	_netdev	0	0

?? netfs ??????

```
## CentOS 7
systemctl enable remote-fs.target
```

```
## CentOS 4/5/6
chkconfig netfs on
```

**?? MTU ??**

????? MTU ? 1500????? iSCSI ?????????? 9000??? Linux ?????????? Switch ? iSCSI Storage (iSCSI Target) ?????  
????

RedHat 7.x)

???????????????? frame ????????

UNSUCCESSFUL

```
# ping -M do -c 4 -s 8196 10.1.1.21
PING 10.1.1.21 (10.1.1.21) 8185(8213) bytes of data.
PING 10.1.1.21(10.1.1.21) 8196(8224) bytes of data.
ping: local error: Message too long, mtu=1500
ping: local error: Message too long, mtu=1500
```

SUCCESSFUL

```
# ping -M do -c 4 -s 1408 10.1.1.21
PING 10.1.1.21 (10.1.1.21) 1408(1436) bytes of data.
1416 bytes from 10.1.1.21: icmp_seq=1 ttl=58 time=224 ms
```

???? MTU (NOTE: ??????)

ip link set dev ens2f0 mtu 9000

????????? iSCSI ????????? ifcfg-ethXX???????

MTU="9000"

?????????

????

?? disk path ????

- ??????? Storage LUN ????
- LUN ??? Size
- Storage ? path ????

[root@bdb7-a ~]# sanlun lun show -p

ONTAP Path: TPEDBISCSISVM01:/vol/BDB7\_A\_2\_vol/BDB7\_A\_2

LUN: 1

LUN Size: 500.1g

Product: cDOT

Host Device: mpath2(3600a0980383136312d3f4e387455564c)

Multipath Policy: service-time 0

Multipath Provider: Native

host	vserver			
path	path	/dev/	host	vserver
state	type	node	adapter	LIF
up	primary	sdo	host12	TPEDBISCSISVM01_iSCSI2
up	primary	sds	host13	TPEDBISCSISVM01_iSCSI2
up	primary	sdaa	host15	TPEDBISCSISVM01_iSCSI1
up	primary	sdae	host16	TPEDBISCSISVM01_iSCSI1
up	secondary	sdg	host10	TPEDBISCSISVM01_iSCSI4
up	secondary	sdk	host11	TPEDBISCSISVM01_iSCSI3
up	secondary	sdw	host14	TPEDBISCSISVM01_iSCSI4
up	secondary	sdc	host9	TPEDBISCSISVM01_iSCSI3

?? multipathd ????????

multipathd show config

?: ?????? Storage???

???? iSCSI connections

```
# iscsiadm -m session --op show
tcp: [1] 10.18.104.32:3260,1038 iqn.1992-08.com.netapp:sn.58042162340f11e9892700a098e3ab45:vs.16
(non-flash)
tcp: [2] 10.18.104.33:3260,1039 iqn.1992-08.com.netapp:sn.58042162340f11e9892700a098e3ab45:vs.16
(non-flash)
tcp: [3] 10.18.104.34:3260,1040 iqn.1992-08.com.netapp:sn.58042162340f11e9892700a098e3ab45:vs.16
(non-flash)
tcp: [4] 10.18.104.34:3260,1040 iqn.1992-08.com.netapp:sn.58042162340f11e9892700a098e3ab45:vs.16
(non-flash)
tcp: [5] 10.18.104.33:3260,1039 iqn.1992-08.com.netapp:sn.58042162340f11e9892700a098e3ab45:vs.16
(non-flash)
tcp: [6] 10.18.104.31:3260,1037 iqn.1992-08.com.netapp:sn.58042162340f11e9892700a098e3ab45:vs.16
(non-flash)
tcp: [7] 10.18.104.31:3260,1037 iqn.1992-08.com.netapp:sn.58042162340f11e9892700a098e3ab45:vs.16
(non-flash)
tcp: [8] 10.18.104.32:3260,1038 iqn.1992-08.com.netapp:sn.58042162340f11e9892700a098e3ab45:vs.16
(non-flash)
```

```
#iSCSI Logout All  
iscsiadm --mode node --logoutall=all
```

```
#iSCSI Login All  
iscsiadm -m node -l
```