



# How to kill Zombie/Defunct process ?

**SOLUTION VERIFIED** - Updated April 29 2015 at 1:16 PM - English



5

## Environment

- Red Hat Enterprise Linux 6
- Red Hat JBoss Enterprise Application Platform (EAP)

## Issue

- How to kill Zombie/Defunct process ?
- Try to stop JBoss EAP but cannot stop as JBoss process become to defunct process.

## Resolution

From the man pages of wait system call:

```

All of these system calls are used to wait for state changes in a child of the calling process, and obtain information about the child whose state has changed. A state change is considered to be: the child terminated; the child was stopped by a signal; or the child was resumed by a signal. In the case of a terminated child, performing a wait allows the system to release the resources associated with the child; if a wait is not performed, then the terminated child remains in a "zombie" state

A child that terminates, but has not been waited for becomes a "zombie". The kernel maintains a minimal set of information about the zombie process (PID, termination status, resource usage information) in order to allow the parent to later perform a wait to obtain information about the child. As long as a zombie is not removed from the system via a wait, it will consume a slot in the kernel process table, and if this table fills, it will not be possible to create further processes. If a parent process terminates, then its "zombie" children (if any) are adopted by init(8), which automatically performs a wait to remove the zombies.

```

There is no other way to clear the zombies from system. To remove zombies, the SIGCHLD signal can be sent to the parent manually, using the kill command. If the parent process still refuses to reap the zombie, the next step would be to remove the parent process. When a process loses its parent, init becomes its new parent. Init periodically executes the wait system call to reap any zombies with init as parent.

Product(s) [Red Hat JBoss Enterprise Application Platform](#) Tags [eap](#) [jboss](#) [jboss\\_eap](#)

This solution is part of Red Hat's fast-track publication program, providing a huge library of solutions that Red Hat engineers have created while supporting our customers. To give you the knowledge you need the instant it becomes available, these articles may be presented in a raw and unedited form.

### People who viewed this solution also viewed

<p><a href="#">How to identify association between parent process and its child sub-process ?</a></p> <p>Solution - 2015年12月16日</p>	<p><a href="#">What is a zombie (defunct) process?</a></p> <p>Solution - 2020年1月30日</p>	<p><a href="#">Jenkins is spawning many zombie processes in my OpenShift cluster</a></p> <p>Solution - 2018年7月25日</p>
---	---	---

### 3 Comments



**Kannan Kunchithapatham** 19 April 2018 10:55 AM

Give example or illustration, just there are only texts

[Reply](#)

NEWBIE  
7 Points



**Airwide Team** 8 February 2019 4:57 AM

Please provide the command to kill the defunct process instead of giving explanation.

[Reply](#)

NEWBIE  
13 Points



**Adolphe Bom** 5 June 2020 2:33 PM

kill <process(s)> is the command the kill processes. You can use it with -9 or -15 options. Example kill -9 109446 or kill -15 109446. Remember you can kill more than one process.

[Reply](#)

COMMUNITY MEMBER  
25 Points



#### QUICK LINKS

- Downloads
- Subscriptions
- Support Cases
- Customer Service
- Product Documentation

#### HELP

- Contact Us
- Customer Portal FAQ
- Log-in Assistance

#### SITE INFO

- Trust Red Hat
- Browser Support Policy
- Accessibility
- Awards and Recognition
- Colophon

#### RELATED SITES

- redhat.com
- openshift.com
- developers.redhat.com
- connect.redhat.com

#### ABOUT

- Red Hat Subscription Value
- About Red Hat
- Red Hat Jobs

