

fail2ban command

?????

- Commands - Fail2ban

| Cmd | Description |
|---|--|
| service fail2ban restart systemctl restart fail2ban | restart fail2ban service (after edit configuration) |
| fail2ban-client reload | restart fail2ban client |
| fail2ban-client status | get list activated jail |
| fail2ban-client status <JAIL> example: fail2ban-client status wplogin example: fail2ban-client status sshd | get <JAIL> status (the number of unsuccessful attempts and the list of banned IPs) |
| fail2ban-regex /var/lib/docker/containers/<CONTAINERID>/<CONTAINERID>-json.log /etc/fail2ban/filter.d/wplogin.conf | test regex wplogin |
| fail2ban-regex /var/log/auth.log /etc/fail2ban/filter.d/sshd.conf | test regex sshd |
| fail2ban-regex "line" "failregex" | test regex |
| fail2ban-client set <JAIL-NAME> unbanip <IP-ADDRESS> | manually unban IP |
| fail2ban-client set <JAIL-NAME> banip <IP-ADDRESS> | manually Ban IP |
| tail -f /var/log/fail2ban.log | view fail2ban logs |
| iptables -L --line-numbers | list IP blocked with line numbers |
| iptables -D <Jail-Name> -s <IP-ADDRESS> -j DROP Example: Jail-Name =f2b-wplogin Jail-Name =f2b-sshd | Unban IP |
| fail2ban-server -b | start fail2ban server |
| docker inspect --format '{{.LogPath}}' \$INSTANCE_ID | return instance log file path |
| fail2ban-client get <JAIL-NAME> ignoreip | Test ignoreip for JAIL |

Check the version

```
fail2ban-client version
```

Check the Help

```
fail2ban-client -h
```

Revision #5

Created 1 July 2022 05:27:27 by Admin

Updated 7 March 2023 11:52:11 by Admin