

# Install Fail2Ban on Debian

## Installation

Download: <https://www.fail2ban.org/wiki/index.php/Downloads>

```
# Debian 7.x
tar xzf 0.9.2.tar.gz
cd fail2ban-0.9.2/
python setup.py install
```

## Verify

```
fail2ban-client -h
```

## Configuration for Asterisk

On Asterisk)

/etc/asterisk/logger.conf:

```
...
[logfiles]
...
fail2ban => notice,warning,security
```

Restart the logger on Asterisk

```
asterisk -rx "logger reload"
asterisk -rx "logger show channels"
```

On Fail2Ban)

/etc/fail2ban/jail.d/asterisk.conf

```
[asterisk]
enabled = true
```

```
logpath = /var/log/asterisk/fail2ban  
maxretry = 5  
bantime = 259200
```

## Configuration for SSH

/etc/fail2ban/jail.d/sshd.conf

```
[sshd]  
enabled = true  
bantime = 7200  
findtime = 900  
maxretry = 4
```

## Auto startup

```
cd fail2ban-0.9.2/  
cp files/debian-initd /etc/init.d/fail2ban  
chmod 0755 /etc/init.d/fail2ban  
update-rc.d fail2ban defaults
```

## Service start

```
service fail2ban start
```

## Setup Logrotate

/etc/logrotate.d/fail2ban

```
/var/log/fail2ban.log {  
    missingok  
    notifempty  
    size 30k  
    create 0600 root root  
    postrotate  
        /usr/bin/fail2ban-client set logtarget /var/log/fail2ban.log 1>/dev/null || true  
    #/usr/bin/fail2ban-client reload 2> /dev/null || true  
    endscript  
}
```

## FAQ

Q:?? Call Log ??????

“ Call from " (195.154.134.116:5071) to extension '8011441295298642' rejected because extension not found in context 'public'.

Ans??? Asterisk ? allowguest=no

?? sip.conf

allowguest=no

Apply the changes

```
#> asterisk -rx "sip reload"  
#> asterisk -rx "sip show settings" | grep -i "Allow unknown access"  
Allow unknown access: No
```

---

Revision #2

Created 9 April 2021 03:34:42 by Admin

Updated 11 November 2021 13:08:38 by Admin