

# patch & diff

????

```
#
diff -uN old.code new.code > patch.file

#
patch < patch.file

#
patch -RE < patch.file
```

??????

```
#
diff -rupN olddir newdir > patch.dir

#
patch -p1 < patch.dir

#
patch -RE -p1 < patch.dir
```

??????????

```
# : asterisk_orig/
# : asterisk_patched/

cd asterisk_orig; find ./ -name "*.c" -exec md5sum -b {} \; > ../asterisk_orig.md5; cd ../
cd asterisk_patched; find ./ -name "*.c" -exec md5sum -b {} \; > ../asterisk_patched.md5; cd
../

diff asterisk_orig.md5 asterisk_patched.md5

273c273
```

```
< 894a111d1efa5901471820e203503039 *. /channels/chan_sip.c
---
> 00116baac23473049b5801c9287fb4be *. /channels/chan_sip.c
```

```
?????? asterisk_orig ? asterisk_patched ??????????????????????????????
asterisk_patched ?????????????? .c ???
```

diff ? curl ???

```
diff <(curl http://somesite/file1) <(curl http://somesite/file2)
```

## Tutorials

- [Understanding of diff output](#)

---

Revision #6  
Created 6 July 2020 03:52:38 by Admin  
Updated 5 August 2022 01:00:30 by Admin