

screen

screen ????

```
[] screen  
#> screen  
  
or  
  
#> screen -S <session-name>  
  
[ ] session  
#> screen -ls  
  
[] (resume) [] session  
#> screen -r <session-id>  
  
[ ] session [ ] deattach [ ] resume  
#> screen -D <session-id>  
#> screen -r <session-id>  
  
[ ] session  
#> screen -X -S <session-id> kill  
  
[] screen [ ] session  
#> exit
```

screen ???? RS232

```
screen /dev/ttyACM0 115200
```

TIP: *???? screen is terminating???? sudo?*

?????

~/.screenrc?

```
# Start message
startup_message off

# Disable vbell
vbell off

# Set hardstatus always on
hardstatus alwayslastline " %-Lw%{= Bw}%n%f %t%{-}%+Lw %=| %M %d %0c:%s "

# Set default encoding using utf8
defutf8 on

#
term xterm

# Set the number of scrollback lines
#defscrollback 10000

# Fix termcapinfo for xterm to allow column resizing
# xterm emulation is used by PuTTY
# Uncomment the line below if running on CentOS 6.x/7.x
#termcapinfo xterm Z0=\E[?3h:Z1=\E[?3l:is=\E[r\E[m\E[2J\E[H\E[?7h\E[?1;4;6l

# Fix termcapinfo for cleaning the terminal after detach
# Uncomment the line below if running on AIX 7.x
#termcapinfo xterm*|rxvt* te=\E[?1049l:ti=\E[?1049h:
```

“ TIPS:

start_message ??????????

vbell ??????? tab ??????

hardstatus ??????????????????????

defscrollback ???????

?? screen ?????

????

?? screen ??? session (deattach)

Ctrl-a + d

?? screen ??? session

Ctrl-a + k

????

????????????????????????

???????????????? space ????????????? space ?????????????

Ctrl-a + [

????????

Ctrl-a +]

?????

???? <Ctrl-a> + |

???? <Ctrl-a> + S

???? <Ctrl-a> + tab

??????? <Ctrl-a> + Q

??????? <Ctrl-a> + X ;????? session

????????

???? screen ???

<Ctrl-a> + c

