

# sudo

- [The Difference Between Su, Sudo Su, Sudo -i, and Sudo -s](#)
- [How To Run All Programs In A Directory Via Sudo In Linux](#)
- [10 Useful Sudoers Configurations for Setting 'sudo' in Linux](#)

????

```
# john SHELL
sudo -u john bash -c "whoami"

# john vnc-H HOME=/root
sudo -H -u john bash -c "vncserver"

# devrpt db2_get_tbs_usage.sh -d devrptdb
sudo -u devrpt -H -s /usr/local/bin/db2_get_tbs_usage.sh -d devrptdb
# 
sudo -u devrpt -H bash -c "/usr/local/bin/db2_get_tbs_usage.sh -d devrptdb"

# 
echo "ThisIsPassword" | sudo -S ls -l /root

# sudo
sudo -l -U <username>
```

????

```
alang ALL=(devrpt) /bin/bash,/usr/local/bin/db2_get_tbs_usage.sh
```

“????:

<?????> <??????????>=<?????> <?????>

????? SHELL Scripts??? scripts ?????????? /bin/bash?

?????????

?????????????????????????????????

```
developer-name ALL=(ALL) NOPASSWD:/usr/bin/sudo,/bin/su - app-user
```

???????

????????????? root ?????????????????????? root ?????? root?

```
# RedHat 7/8, /etc/sudoers.d/sysadmin  
your-account ALL=(ALL) ALL
```

“ “ ? root ????? root ??

```
# RedHat 6/7/8  
# ooooooooooooooo  
sudo -i  
sudo su -  
  
# RedHat 4  
sudo su -  
# Or  
sudo -s # NOTE: not root's profile
```

“ “ sudo -i ??? /usr/local/bin ???

????? root ?? `visudo`

```
Defaults secure_path = /sbin:/bin:/usr/sbin:/usr/bin:/usr/local/bin
```

????? `/root/.bash_profile`

```
# Custom PATH  
case :$PATH: in  
*:/:/usr/local/bin/*);;
```

```
*) PATH=/usr/local/bin:$PATH ;;
esac
export PATH
```

## Disable 'su'

### Disable 'su' Access for Sudo Users in Linux

**visudo :**

```
# Cmnd alias spceification
Cmnd_Alias DISABLE_SU = /bin/su

# Disable the su for the user trendoceans
trendoceans ALL=ALL, !DISABLE_SU
```

## logfile

**visudo :**

```
# Log File:
Defaults    logfile="/var/log/sudo.log"
```

---

Revision #21  
Created 1 June 2021 08:07:13 by Admin  
Updated 21 February 2024 16:48:30 by Admin