

FAQ

Q: ????? node ??

```
Application rabbit exited with reason:  
{could_not_write_file,"/var/lib/rabbitmq/mnesia/rabbit@tpeeaprmq982/cluste  
r_nodes.config",enospc},{rabbit,start,[normal,[]]}
```

Solution:

???????????????? /var/lib/rabbitmq/mnesia ?? node ??????

```
[root@tpeeaprmq981 ~]# df -h  
Filesystem      Size  Used Avail Use% Mounted on  
devtmpfs        1.8G   0 1.8G   0% /dev  
tmpfs           1.8G  4.0K 1.8G   1% /dev/shm  
tmpfs           1.8G  24M 1.8G   2% /run  
tmpfs           1.8G   0 1.8G   0% /sys/fs/cgroup  
/dev/mapper/rootvg-rootlv 9.0G  4.0G  5.1G  45% /  
/dev/sda2       1014M 344M 671M  34% /boot  
/dev/sda1       599M  5.8M 594M   1% /boot/efi  
/dev/mapper/rootvg-mqdatalv 5.0G  5.0G  20K 100% /var/lib/rabbitmq  
/dev/mapper/rootvg-homelv 507M  30M 478M   6% /home  
/dev/mapper/rootvg-worktmp 507M  46M 462M   9% /worktmp  
/dev/mapper/rootvg-optlv 2.0G 997M 1.1G  49% /opt  
tmpfs           364M   0 364M   0% /run/user/0  
[root@tpeeaprmq981 ~]#  
[root@tpeeaprmq981 ~]#  
[root@tpeeaprmq981 ~]# du -csh /var/lib/rabbitmq/mnesia/*  
204K  /var/lib/rabbitmq/mnesia/rabbit@rmq981  
4.0K  /var/lib/rabbitmq/mnesia/rabbit@rmq981-feature_flags  
0     /var/lib/rabbitmq/mnesia/rabbit@rmq981-plugins-expand  
300K  /var/lib/rabbitmq/mnesia/rabbit@tpeeaprmq98  
5.0G  /var/lib/rabbitmq/mnesia/rabbit@tpeeaprmq981  
4.0K  /var/lib/rabbitmq/mnesia/rabbit@tpeeaprmq981-feature_flags
```

```
0 /var/lib/rabbitmq/mnesia/rabbit@tpeeaprmq981-plugins-expand
4.0K /var/lib/rabbitmq/mnesia/rabbit@tpeeaprmq98-feature_flags
0 /var/lib/rabbitmq/mnesia/rabbit@tpeeaprmq98-plugins-expand
5.0G total
```

```
[root@tpeeaprmq981 ~]# rm -rf /var/lib/rabbitmq/mnesia/rabbit@tpeeaprmq981
[root@tpeeaprmq981 ~]# rm /var/lib/rabbitmq/mnesia/rabbit@tpeeaprmq981-feature_flags
rm: remove regular file '/var/lib/rabbitmq/mnesia/rabbit@tpeeaprmq981-feature_flags'? y
[root@tpeeaprmq981 ~]#
[root@tpeeaprmq981 ~]# rm /var/lib/rabbitmq/mnesia/rabbit@tpeeaprmq981-plugins-expand
rm: cannot remove '/var/lib/rabbitmq/mnesia/rabbit@tpeeaprmq981-plugins-expand': Is a directory
[root@tpeeaprmq981 ~]# rm -rf /var/lib/rabbitmq/mnesia/rabbit@tpeeaprmq981-plugins-expand
```

Q: ??? Cluster

[error] Node rabbit@tpeeaprmq98 thinks it's clustered with node rabbit@tpeeaprmq982, but rabbit@tpeeaprmq982 disagrees

Solution:

? node rabbit@tpeeaprmq98 ?? `rabbitmqctl cluster_status` ?????? node rabbit@tpeeaprmq982 ????????????

```
# On the node rabbit@tpeeaprmq98
rabbitmqctl forget_cluster_node rabbit@tpeeaprmq982
```

Q: Network partition detected

Web UI ????????

Overview INDUCTORS

Network partition detected

Mnesia reports that this RabbitMQ cluster has experienced a network partition. There is a risk of losing data. Please read RabbitMQ documentation about network partitions and the possible solutions.

The nature of the partition is as follows:

Node	Was partitioned from
rabbit@tpeeaprmq98	rabbit@tpeeaprmq982
rabbit@tpeeaprmq981	rabbit@tpeeaprmq982
rabbit@tpeeaprmq982	rabbit@tpeeaprmq98 rabbit@tpeeaprmq981

While running in this partitioned state, changes (such as queue or exchange declaration and binding) which take place in one partition will not be visible to other partition(s). Other behaviour is not guaranteed.

Node ?? `rabbitmqctl cluster_status` ?? Network Partitions

Network Partitions

Node rabbit@tpeeaprmq98 cannot communicate with rabbit@tpeeaprmq982

Node rabbit@tpeeaprmq981 cannot communicate with rabbit@tpeeaprmq982

???tpeeaprmq982 ?????????????????? node ??????????Cluster ??? Network Partition
??(aka split-brain ?????)???? quorum queue ??????????????????

???????? Network Partition ????

- ?????: Clustering and Network Partitions — RabbitMQ

??????? Node tpeeaprmq982 ???

```
rabbitmqctl stop  
systemctl start rabbitmq-server
```

