SSL ? CA

SSL ???? Secure Sockets Layer?? (??????????)?????????? (????????????????????????)? ????? - Certificate Authority (CA)???????????SSL??????? Server ? Root ???? ???????????????????? Verisign ?? CA ???? Linux ? Windows ???????? Linux ????Windows ?????? Windows ???Certificate Service?

- Links to Tutorials
- SSL ????
- SSL/TLS Web Server

Links to Tutorials

Let's Encrypt

- How To Secure Apache with Let's Encrypt on Ubuntu 16.04
- SSL For Free ?? SSL ??????? Let’s Encrypt ???????
- How to Use Let’s Encrypt to Install Free SSL Certificates on Your Linux VPS
- Apache with Let’s Encrypt Certificates on CentOS 8
- How to manage Let's Encrypt SSL/TLS certificates with certbot
- certbot
- How to issue Let’s Encrypt wildcard certificate with acme.sh and Cloudflare DNS
- How to forcefully renew Let’s Encrypt certificate
- How to Check Let’s Encrypt SSL Certificate Expiration Date
- [Nginx] Create a Web Server with NGINX and Secure it Using Certbot

Certbun - Certbot alternative

- More On Installing And Configuring Certbun For Use With Apache

Test SSL - ???????? SSL ???????

- https://www.tecmint.com/testssl-sh-test-tls-ssl-encryption-in-linux-commandline/
- https://github.com/drwetter/testssl.sh
- https://testssl.sh/
- https://www.ssllabs.com/ssltest/
- https://github.com/Matty9191/ssl-cert-check

Monitoring SSL

- https://certificatemonitor.org
  Source code: https://github.com/RaymiiOrg/certificate-expiry-monitor
- https://alerts.httpscop.com

SSL Certificates

- mkcert - A simple tool for making locally-trusted development certificates. It requires no configuration.
  - How to create locally trusted SSL Certificates on Linux and macOS with mkcert
  - How to Create Locally Trusted SSL Certificates with mkcert on Ubuntu 20.04
- SSL Certificates Cheat-Sheet

ACME (Automated Certificate Management Environment)

ACME ??????????????????IETF??ACME??

- Step Certificates
- Self-Host ACME Server
- Run your own private CA & ACME server using step-ca

SSL ????

Check TLS/SSL certificate expiration date

from a website)

```
# NOTE: openssl requires at least 1.1.1
SITE_URL="www.cloudcoin.global"
SITE_SSL_PORT="443"
## note echo added ##
echo | openssl s_client -servername ${SITE_URL} -connect ${SITE_URL}:${SITE_SSL_PORT} \
| openssl x509 -noout -dates
# Alternaively
openssl s_client -connect ${SITE_URL}:${SITE_SSL_PORT} -servername ${SITE_URL} 2> /dev/null | openssl
x509 -noout -dates
```

output

```
depth=2 C = IE, O = Baltimore, OU = CyberTrust, CN = Baltimore CyberTrust Root
verify return:1
depth=1 C = US, O = "Cloudflare, Inc.", CN = Cloudflare Inc ECC CA-3
verify return:1
depth=0 C = US, ST = CA, L = San Francisco, O = "Cloudflare, Inc.", CN = cloudcoin.global
verify return:1
DONE
notBefore=Jun  5 00:00:00 2020 GMT
notAfter=Jun  5 12:00:00 2021 GMT
```

- **s_client** : The s_client command implements a generic SSL/TLS client which connects to a remote host using SSL/TLS.
- **-servername** $DOM : Set the TLS SNI (Server Name Indication) extension in the ClientHello message to the given value. *NOTE: openssl requires at lease 1.1.1*
- **-connect** $DOM:$PORT : This specifies the host ($DOM) and optional port ($PORT) to connect to.
- **x509** : Run certificate display and signing utility.
- **-noout** : Prevents output of the encoded version of the certificate.
- **-dates** : Prints out the start and expiry dates of a TLS or SSL certificate.

from a PEM encoded certificate file)

```
openssl x509 -enddate -noout -in /etc/nginx/ssl/www.cyberciti.biz.fullchain.cer

# find out if the TLS/SSL certificate expires within next 7 days (604800 seconds):
openssl x509 -enddate -noout -in my.pem -checkend 604800
```

output

```
notAfter=Dec 29 23:48:42 2020 GMT
```

Shell script to alert sysadmin

```
#!/bin/bash
# Purpose: Alert sysadmin/developer about the TLS/SSL cert expiry date in advance
# Author: Vivek Gite {https://www.cyberciti.biz/} under GPL v2.x+
# ------------------------------------------------------------------------------
PEM="/etc/nginx/ssl/letsencrypt/cyberciti.biz/cyberciti.biz.fullchain.cer"

# 7 days in seconds
DAYS="604800"

# Email settings
_sub="$PEM will expire within $DAYS (7 days)."
_from="system-account@your-dommain"
_to="sysadmin@your-domain"
_openssl="/usr/bin/openssl"
$_openssl x509 -enddate -noout -in "$PEM"  -checkend "$DAYS" | grep -q 'Certificate will expire'

# Send email and push message to my mobile
if [ $? -eq 0 ]
then
echo "${_sub}"
        mail -s "$_sub" -r "$_from" "$_to" <<< "Warning: The TLS/SSL certificate ($PEM) will expire soon on $HOSTNAME [$(date)]"
        # See https://www.cyberciti.biz/mobile-devices/android/how-to-push-send-message-to-ios-and-android-from-linux-cli/ #
        source ~/bin/cli_app.sh
        push_to_mobile "$0" "$_sub. See $_to email for detailed log. -- $HOSTNAME " >/dev/null
fi
```

With Python

- How to prevent TLS certificates from expiring with Python (activestate.com)

Get the Server certificate from the website

NOTE: openssl requires at least 1.1.1

```
echo -n | openssl s_client -showcerts -servername some.web.site -connect some.web.site:443 | sed -ne '/-BEGIN CERTIFICATE-/,/-END CERTIFICATE-/p' > some-web-site.pem
```

> ???? openssl ??????? Firefox ? Chrome ???? Server ????

????? *.crt, *.pem ?????

??????????? -----BEGIN CERTIFICATE----- ? -----END CERTIFICATE----- ????????????????????? `openssl` ???

```
openssl x509 -text -noout -in my_CA.pem
```

Check the TLS version

```
nmap --script ssl-enum-ciphers -p 443 www.google.com


# -tls1 for TLSv1
# -tls1_1 for TLSv1.1
# -tls1_2 for TLSv1.2
openssl s_client -connect www.google.com:443 -tls1_3
```

Generate a CSR (Certificate Signing Request)

```
sudo apt install openssl  #[On Debian/Ubuntu]
sudo yum install openssl  #[On CentOS/RHEL]
sudo dnf install openssl  #[On Fedora]


openssl req -new -newkey rsa:2048 -nodes -keyout example.com.key -out example.com.csr
```

Show the Information of the certificate

```
openssl x509 -noout -text -in your.cer

# For the cert file that is generated by Windows
openssl x509 -noout -text -inform der -in win.cer
```

More commands

```
# Generating a Private Key
openssl genpkey -algorithm RSA -out private.key

# Generating a Certificate Signing Request (CSR)
openssl req -new -key private.key -out csr.csr

# Generating a Self-Signed Certificate
openssl req -new -x509 -key private.key -out certificate.crt -days 365

# Encrypting Files
openssl enc -aes256 -in sensitive.txt -out sensitive.enc

# Decrypting Files
openssl enc -aes256 -d -in sensitive.enc -out sensitive.txt

# Converting Certificate Formats
openssl x509 -in certificate.crt -out certificate.pem

# Creating a Certificate Chain
cat intermediate.crt root.crt > chain.crt

# Signing a CSR with a CA
openssl x509 -req -in csr.csr -CA ca.crt -CAkey ca.key -CAcreateserial -out certificate.crt -days 365

# Generating a Random Number
openssl rand -hex 16

# Checking CSR Details
openssl req -in csr.csr -noout -text

# Viewing Certificate Expiry
openssl x509 -enddate -noout -in certificate.crt
```

```
# Converting PFX to PEM
openssl pkcs12 -in certificate.pfx -clcerts -nokeys -out certificate.pem

# Creating a Password-Protected Private Key
openssl genpkey -algorithm RSA -aes256 -out private.key

# Testing SSLv2/v3 Protocol Support
openssl s_client -connect example[dot]com:443 -ssl2/-ssl3

# Extracting Public Key from Private Key
openssl rsa -in private.key -pubout -out public.key

# Encrypting and Decrypting Files with a Passphrase
# Encrypting File:
openssl enc -aes256 -salt -in sensitive.txt -out sensitive.enc
# Decrypting File:
openssl enc -aes256 -d -in sensitive.enc -out sensitive_decrypted.txt
```

SSL/TLS Web Server

Generate Certificates

Method 1: ??? CA ???

```
mkdir /etc/apache2/certs
cd /etc/apache2/certs
openssl genrsa -out myhomepbx.key 2048
openssl req -new -key myhomepbx.key -out myhomepbx.csr
openssl x509 -req -days 3650 -in myhomepbx.csr -signkey myhomepbx.key -out myhomepbx.crt
```

Method 2: ?? CA ???

```
# generate CA
# organizationName = HomePBX
# commName = HomePBX CA
# Enter PEM pass phrase: set new password that is used to sign the certicficate.
cd /etc/ssl/homepbxCA
openssl req -new -x509 -extensions v3_ca -keyout ca.key -out ca.crt -days 3650

# prerequisites
# Edit the openssl.homepbx.cnf as required
cp /etc/ssl/openssl.conf ./openssl.homepbx.cnf
touch index.txt
echo '01' > serial
mkdir newcerts

# generate Server certificates
# organizationName = HomePBX (it must be the same as CA, otherwise it cannot be signed by the CA)
# commName = FQDN of website or *
# Enter PEM pass phrase: It's not required, enter to skip it if wanted.
openssl req -config openssl.homepbx.cnf -new -nodes -keyout server.key -out server.csr
openssl ca -config openssl.homepbx.cnf -days 3650 -in server.csr -out server.crt

# generate PKCS12 for client authentication
# NOTE: you can create PKCS12 file by either server certificate or CA certificate.
```

```
# Enter Export Password: set new pasword that is used for importing the PKCS12
openssl pkcs12 -export -clcerts -in ca.crt -inkey ca.key -out homepbx_2021y.p12
# Alternatively
openssl pkcs12 -export -clcerts -in server.crt -inkey server.key -out homepbx_2021y.p12
```

openssl.homepbx.cnf

```
...
[ CA_default ]

dir            = .            # Where everything is kept  <== Here
certs          = $dir/certs           # Where the issued certs are kept
crl_dir        = $dir/crl             # Where the issued crl are kept
database       = $dir/index.txt       # database index file.
#unique_subject = no                  # Set to 'no' to allow creation of
                                      # several certs with same subject.
new_certs_dir  = $dir/newcerts        # default place for new certs.

certificate    = $dir/ca.crt   # The CA certificate <== Here
serial         = $dir/serial          # The current serial number
crlnumber      = $dir/crlnumber       # the current crl number
                                      # must be commented out to leave a V1 CRL
crl            = $dir/crl.pem         # The current CRL
private_key    = $dir/ca.key# The private key  <== Here

x509_extensions = usr_cert             # The extensions to add to the cert
...
```