

SSL/TLS Web Server

Generate Certificates

Method 1: ??? CA ???

```
mkdir /etc/apache2/certs
cd /etc/apache2/certs
openssl genrsa -out myhomepbx.key 2048
openssl req -new -key myhomepbx.key -out myhomepbx.csr
openssl x509 -req -days 3650 -in myhomepbx.csr -signkey myhomepbx.key -out myhomepbx.crt
```

Method 2: ?? CA ???

```
# generate CA
# organizationName = HomePBX
# commName = HomePBX CA
# Enter PEM pass phrase: set new password that is used to sign the certicficate.
cd /etc/ssl/homepbxCA
openssl req -new -x509 -extensions v3_ca -keyout ca.key -out ca.crt -days 3650

# prerequisites
# Edit the openssl.homepbx.cnf as required
cp /etc/ssl/openssl.conf ./openssl.homepbx.cnf
touch index.txt
echo '01' > serial
mkdir newcerts

# generate Server certificates
# organizationName = HomePBX (it must be the same as CA, otherwise it cannot be signed by the
CA)
# commName = FQDN of website or *
# Enter PEM pass phrase: It's not required, enter to skip it if wanted.
openssl req -config openssl.homepbx.cnf -new -nodes -keyout server.key -out server.csr
openssl ca -config openssl.homepbx.cnf -days 3650 -in server.csr -out server.crt
```

```
# generate PKCS12 for client authentication
# NOTE: you can create PKCS12 file by either server certificate or CA certificate.
# Enter Export Password: set new password that is used for importing the PKCS12
openssl pkcs12 -export -clcerts -in ca.crt -inkey ca.key -out homepbx_2021y.p12
# Alternatively
openssl pkcs12 -export -clcerts -in server.crt -inkey server.key -out homepbx_2021y.p12
```

openssl.homepbx.cnf

```
...
[ CA_default ]

dir                = .                # Where everything is kept <== Here
certs              = $dir/certs        # Where the issued certs are kept
crl_dir            = $dir/crl          # Where the issued crl are kept
database           = $dir/index.txt    # database index file.
#unique_subject    = no                # Set to 'no' to allow creation of
                                        # several certs with same subject.
new_certs_dir      = $dir/newcerts     # default place for new certs.

certificate        = $dir/ca.crt       # The CA certificate <== Here
serial             = $dir/serial        # The current serial number
crlnumber          = $dir/crlnumber    # the current crl number
                                        # must be commented out to leave a V1 CRL
crl                = $dir/crl.pem      # The current CRL
private_key        = $dir/ca.key# The private key <== Here

x509_extensions   = usr_cert          # The extensions to add to the cert
...
```

Revision #26

Created 2021-10-16 10:59:22 CST by A-Lang (Admin)

Updated 2023-04-11 10:54:57 CST by A-Lang (Admin)